

Test Report

No.SDHL2308013627FT

Date: Aug 11, 2023

Page 1 of 12

GUANGZHOU DECO SEATING CO.,LTD
ROOM 1203, 12 FLOOR, MAIN TOWER OF GUANGDONG INTERNATIONAL HOTEL,
NO. 339 HUANSI EAST ROAD, GUANGZHOU, GUANGDONG, P.R.CHINA

Sample Description : DROP TWO SEATER SOFA BIG VERSION
Style No. : DROP TWO SEATER SOFA BIG VERSION
Item No. : DA763RO
SKU No. : DA763RO
Country of Origin : CHINA

As above test item and its relevant information regarding to the submission are provided and confirmed by the applicant. SGS is not liable to either the test item or its relevant information, in terms of the accuracy, suitability, reliability or/and integrity accordingly.

Sample Receiving Date : Aug 02, 2023
Test Performing Date : Aug 02, 2023 to Aug 11, 2023
Test Performed : Selected test(s) as requested by applicant

Test Result Summary

No.	Test(s) Requested	Result(s)	Comments
1	UNE-EN 581-1:2017	PASS	/
2	UNE-EN 581-2:2016/AC:2016 (Contract), excluding Information for use	PASS	/
3	UNE-EN 1022:2019	PASS	/

For further details, please refer to the following page(s)

Signed for and on behalf of
SGS-CSTC Standards Technical Services Co., Ltd. Shunde Branch

Marco Leung

Marco Leung
Authorized Signatory

scan to see the report



SDHL2308013627FT



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

1-2/F., Building 1, European Industrial Park, No.1, Shunhe South Road, Wusha, Daliang, Shunde District, Foshan, Guangdong, China 528300 t (86-757)22805888 www.sgs.com.cn
中国·广东·佛山市顺德区大良街道办事处五沙社区居民委员会顺和南路1号欧洲工业园一号厂房首层、二层 邮编: 528300 t (86-757)22805888 sgs.china@sgs.com

TESTS AND RESULTS
Part 1. Test Conducted:

UNE-EN 581-1:2017 Outdoor furniture--seating and tables for camping, domestic and contract use—Part 1. General safety requirements.

No. of Sample:

1 piece (Sample #1). For more sample information and pictures, please refer to the following page.

Test and Requirements	Test Results
5 Safety requirements	
5.1 General In order to avoid physical injury when the product is in its intended position of use, all edges and corners shall be rounded, chamfered or otherwise protected. This applies to: - Seating: Edges of the seat, back rest and arm rests and any part of the bottom surface of the seat at a distance less than 120 mm from any edge, where a finger can commonly access; - Tables: Table tops, any part of the underside of the top surface at a distance less than 500 mm from any edge below the table, where a knee and/or an arm can commonly access. All other parts shall be free from burrs, sharp edges and sharp points. Movable and adjustable parts shall be designed so that injuries and inadvertent operation are avoided. It shall not be possible for any load bearing part of the furniture to come loose unintentionally. All parts which are lubricated to assist sliding shall be designed to protect users from lubricant stains when in normal use.	PASS
5.2 Tubular components There shall be no accessible holes in the ends of tubular components with a diameter between 7 mm to 12 mm and with a depth more or equal to 10 mm. The bottom of tubular legs in contact with the floor shall be closed or capped, however, holes in them are allowed as long as they are not between 7 and 12 mm.	PASS
5.3 Shear and squeeze points	
5.3.1 Shear and squeeze points when erecting, adjusting and folding away Unless 5.3.2 or 5.3.3 are applicable, shear and squeeze points that are created only during erecting, adjusting or folding away are acceptable providing the user can be assumed to be in control of his/her movements and to be able to cease applying the force immediately on experiencing pain.	N/A
5.3.2 Shear and squeeze points under the influence of powered mechanisms There shall be no accessible shear and squeeze points created by parts of the furniture operated by powered mechanisms, e.g. mechanical springs and gas lifts.	N/A
5.3.3 Shear and squeeze points during use There shall be no accessible shear and squeeze points created by loads applied during normal use. Shear and squeeze points are not acceptable if there is a risk of injury created by the weight of the user during normal movements and actions, e.g. attempting to move the seating by lifting the seat or by adjusting the backrest.	PASS



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.
Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com
1-2/F, Building 1, European Industrial Park, No.1, Shunhe South Road, Wusha, Daliang, Shunde District, Foshan, Guangdong, China 528300 t (86-757) 22805888 www.sgs.com.cn
中国·广东·佛山市顺德区大良街道办事处五沙社区居民委员会顺和南路1号欧洲工业园一号厂房首层、二层 邮编: 528300 t (86-757) 22805888 sgs.china@sgs.com

Part 2. Test Conducted:

UNE-EN 581-2:2016/AC:2016 Outdoor furniture – Seating and tables for camping, domestic and contract use – Part 2: Mechanical safety requirements and test methods for seating, excluding Information for use.

No. of Sample:

1 piece (Sample #1). For more sample information and pictures, please refer to the following page.

Test Severity: Contract Level. For the test severity in relation to applications, please refer to Annex A.

Test and Requirements	Test Results
7 Safety, strength and durability requirements for other seating	
7.1 General Before and after the strength, durability and stability tests are carried out, the requirements of UNE-EN 581-1 shall be fulfilled.	PASS
7.2 Stability, strength and durability (With reference to the test methods of UNE EN 1022:2005 and UNE EN 1728:2012/AC:2013 D/E/F) The seating shall be tested for strength, durability and stability following the order listed in Table 2. The safety, strength and durability requirements are fulfilled after testing in accordance with Table 2 when: a) there are no fractures of any joint, member or component, b) there is no loosening of joints intended to be rigid, c) the seating fulfils its function after removal of the test loads, d) the seating fulfils the safety requirements, e) the product shall not overturn when subjected to the stability tests.	
6.4 Seat static load and back static load test Only the vertical seat static force shall be applied to items without a back rest. Apply the downward force of 2000N at the seat loading position. With the downward force maintained, apply the back force of 560N at back loading position, and the back force shall not less than 500N. For the seat not being tested load with 750N. Remove the back load and then the seat load. Repeat above operation for 10 cycles followed by an additional cycle with 30min ± 10s. <i>Note: If seat and back are of one piece of flexible material, only the tests on seat shall be carried out.</i>	PASS
6.5 Seat front edge static load Apply the vertical force of 1300N using the seat loading pad at a point on the seat centre line 100 mm inwards from the front edge of the structure. For the seat not being tested load with 750N. Repeat above operation for 10 cycles.	PASS
6.17 Combined seat and back durability test Only the vertical seat durability force shall be applied to items without a back rest. Apply the downward force of 1000N at the seat loading position. With the downward force maintained, apply the back force of 333N at back loading position. Remove the back load and then the seat load, and the back force shall not less than 300N. For the seat not being tested load with 750N. Repeat above operation for 50000 cycles.	PASS
6.19 Durability test on seating with a multi-position back rest Place the seating in normal use position, with the back rest in the most adverse position. Apply the load of 750N on the seat loading point. Apply rearwards alternating forces of 250N perpendicularly to the back rest, the height of the back rest loading points shall be 100 mm above the back loading point. They shall be 50 mm from the right and left outer edges of the back rest. Repeat above operation for 20000 cycles. <i>Note: This test is only applicable to seating with three or more manually adjustable reclined positions of the backrest.</i>	N/A



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.
Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com
1-2/F, Building 1, European Industrial Park, No.1, Shunhe South Road, Wusha, Daliang, Shunde District, Foshan, Guangdong, China 528300 t (86-757)22805888 www.sgsgroup.com.cn
中国·广东·佛山市顺德区大良街道办事处五沙社区居民委员会顺和南路1号欧洲工业园一号厂房首层、二层 邮编: 528300 t (86-757)22805888 sgs.china@sgs.com

Test and Requirements	Test Results
6.11 Arm rest downwards static load test For seating which only has one arm rest, or which has two arm rests where the distance between the centre of the arm rests is more than 1000 mm, apply the vertical force of 900N at the points along the arm rest most likely to cause failure, but not less than 100 mm from the end of the arm rest structure. For seating with two arm rests, where the distance between the centre of the arm rests is 1 000 mm or less, apply the vertical force simultaneously to both arm rests. For seating with three or more arm rests, carry out the test on one pair of adjacent arm rests. All different arm rest designs shall be tested. Repeat above operation for 10 cycles. <i>Note: If the armrest is less than 15mm wide, carry out test with 700N for contract use.</i>	PASS
6.20 Arm rest durability test The test load of 400 N shall be applied simultaneously on two points for 30000 cycles, at the point most likely to cause failure, but not less than 100 mm from the front or rear edge of the arm rest length and through the centre of the width of the arm rest, but not more than 100 mm from the inner edge of the arm rest. The force shall be applied at an angle of $(10 \pm 1)^\circ$ to the vertical, and to both arm rests simultaneously for seating with only one seating position and to one arm rest only for seating with multiple seating positions.	PASS
6.15 Leg forward static load test For seating with a single seat, apply the seat load of 1000N at the seat loading position to all seat positions. Apply the horizontal force of 400N centrally to the rear of the seat, at seat level, in a forward direction, and this force shall not less than 250N. For seating with multiple seating positions, apply the horizontal force of the most adverse seat position. For seating with only three legs, one foot on the fore and aft centre line of the item of seating and one other foot shall be restrained by stops. Repeat above operation for 10 times.	PASS
6.16 Leg sideways static load test Apply the seat load of 1000N at a suitable position not more than 150mm from the unload edge of the seat. Apply a horizontal force of 300N centrally to the unrestrained side of the seat, at seat level, in a direction towards the restrained feet, and this force shall not less than 200N. For seating with only three legs, one foot on the fore and aft centre line of the item of seating and one other foot shall be restrained by stops. Repeat above operation for 10 times.	PASS
6.24 Seat impact test Allow the seat impactor to fall freely from the height of 240mm to the seat loading position, Repeat the test at one other position considered likely to cause failure, but not less than 100 mm from the front edge of the seat. For multiple seating units, apply the test to one end seat and an intermediate seating position. Repeat above operation for 10 times. <i>Note: This test shall not be carried out on seating with a seat height > 600mm.</i>	PASS
6.8 Foot rest static test Apply the specified downward force to the seat at the seat loading point. Apply a vertical force of 1200N by means of the local loading pad acting 80 mm from front edge of the load bearing structure of the foot rest at those points most likely to cause failure. For round cross section ring shaped footrests, the force shall be applied through the centre of the ring cross section. Repeat above operation for 10 cycles. <i>Note: This test is carried out only on seating with a seat height > 700mm.</i>	N/A



Test and Requirements	Test Results
6.2 Forwards overbalancing, all seating Apply a force $F_v = 600$ N vertically (for multiple sitting places to a maximum of 2 places) by means of the loading pad acting at those points 60 mm behind the front edge of the load bearing structure most likely to result in overturning. At each loaded position apply a force $F_H = 20$ N for at least 5 s horizontally outwards along a horizontal line extended forward from the point where the base of the loading pad meets the upper surface of the seat.	PASS
6.3 Forwards overturning for seating with footrest For seating with footrests repeat the procedure in 6.2 applying the vertical and horizontal loads to the footrests. For footrests of tubular construction the loads shall be applied along the centre line of the tube.	N/A
6.4 Sideways overbalancing, all seating without arms Apply a force $F_v = 600$ N vertically by means of the loading pad at those points 60 mm behind the edge of the load bearing structure of the side nearest the stopped feet most likely to result in overturning. Apply a sideways force $F_H = 20$ N horizontally outwards for at least 5 s along a line from the point where the base of the loading pad meets the upper surface of the seat.	N/A
6.5 Sideways overbalancing, all seating with arms Apply a vertical force $F_1 = 350$ N by means of the loading pad at a position on the centre line of the arm up to a maximum 40 mm inwards from the outer edge of the arm structure at the most adverse position along its length. Apply a vertical force $F_2 = 250$ N at a point 100 mm to the side of the fore and aft centre line of the seat which is nearest the stopped feet and at the same distance from the backrest as the arm loads. Apply a horizontal force $F_H = 20$ N outwards, and perpendicular to the line joining the stopped feet, for at least 5 s, at the upper surface of the armrest in line with the vertical arm force and on the side with stopped feet.	PASS
6.6 Rearwards overbalancing, all seating with backs All adjustable backs shall be set in their most upright position. Apply a vertical force $F_v = 600$ N to the seat by means of the loading pad at the seat loading point (A) determined by the loading point template. Determine the distance (H) in millimeters between the loaded seat and the floor. - For seating having a value of $H \geq 720$ mm uses a force $F_H = 80$ N. - For seating having a value of $H < 720$ mm calculate the force F, in newtons, required from the following formula: $F_H = 0, 2857 (1000-H)$. Where: H is in millimeters; F is in newtons. Apply the force F horizontally for at least 5 s in a rearward direction to the back of the seating at the point (B) determined by the loading point template, or at the top edge of the back rest, whichever is the lower. When the seating has more than one sitting place, carry out the procedure on two most adverse sitting places simultaneously.	PASS
7.7 Reclining chairs without footrest The test method applies to all values of $\theta \geq 10$ and values of γ between 90° and 170° . Load the back of the chair with 8 loading discs (10 kg) by means of the support device (4.5) and place three loading discs onto the front of the seat of the chair at a distance X from the intersection of the seat and back.	N/A
8 Information for use	



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

1-2/F., Building 1, European Industrial Park, No.1, Shunhe South Road, Wusha, Daliang, Shunde District, Foshan, Guangdong, China 528300 t (86-757) 22805888 www.sgs.com.cn
 中国·广东·佛山市顺德区大良街道办事处五沙社区居民委员会顺和南路1号欧洲工业园一号厂房首层、二层 邮编: 528300 t (86-757) 22805888 sgs.china@sgs.com

Test and Requirements	Test Results
8.1 General Instruction for use shall be provided in the language(s) of the country where the seating are sold. These instructions shall be headed "IMPORTANT, RETAIN FOR FUTURE REFERENCE: READ CAREFULLY" in letters no less than 5 mm high, unless if the following information are permanently marked on the product. It shall contain at least the following details: a) name and address of the manufacturer/supplier/retailer; b) conditions for use of the product (domestic, camping or contract). If applicable: c) assembly instructions; d) instructions for the care and maintenance of the seating; e) if the seating is fitted with seat height adjustments with energy accumulators, an additional note is required pointing out that only trained personnel may replace or repair seat height adjustment components with energy accumulators.	N/R

Annex A: Classification of Test severity in relation to applications

- **Outdoor seating for contract use.** Outdoor seating intended for non-private use in places with public access.
- **Outdoor seating for domestic use.** Outdoor seating intended for private use in places use without public access.
- **Outdoor seating for camping use.** Outdoor seating foldable or knock-down and light-weight, intended for use in connection with camping and travelling.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

1-2/F., Building 1, European Industrial Park, No.1, Shunhe South Road, Wusha, Daliang, Shunde District, Foshan, Guangdong, China 528300 t (86-757)22805888 www.sgs.com.cn
 中国·广东·佛山市顺德区大良街道办事处五沙社区居民委员会顺和南路1号欧洲工业园一号厂房首层、二层 邮编: 528300 t (86-757)22805888 sgs.china@sgs.com

Part 3. Test Conducted:

UNE-EN 1022:2019 Furniture - Seating - Determination of stability.

No. of Sample:

1 piece (Sample #1). For more sample information and pictures, please refer to the following page.

Test and Requirements	Test Results
7 Test methods for assessing stability of seating except loungers	
7.1 General The stability tests defined in Clause 7 are not applicable to seating which has both the height of the seat loading point < 200 mm and a mass < 5 kg. Position the seating on the floor with its components as specified in Table 1.	
7.2 Requirements When tested according to 7.3 and 7.4, the seating shall not overturn. Where loads are not specified in other standards the requirements contained in Table B.1 shall be used.	
7.3.1 Forwards overbalancing, all seating Position the seating on the floor surface with two adjacent supporting points on the front or base restrained by stops. Apply a force of 600 N vertically (for multiple sitting places to a maximum of 2 places, simultaneously) by means of the loading pad acting at those points 60 mm behind the front edge of the load bearing structure most likely to result in overturning. At each loaded position apply a force of 20 N for at least 5 s horizontally outwards along a horizontal line extended forward from the point where the base of the loading pad meets the upper surface of the seat. For items of seating with a leg rest attached to the structure of the item, and where the leg rest is designed to support the weight of the user, the test procedure shall be repeated with the leg rest fully extended and the force of 600 N vertically by means of the loading pad acting at the point on the centre line of the leg rest 60 mm behind the front edge of the load bearing structure. For items of seating with a leg rest not designed to support the weight of the user the test is not applicable to the leg rest.	PASS
7.3.2 Forwards overturning for seating with footrest For seating with foot rests of tubular construction, or where the foot rest depth is less than 120 mm, repeat the procedure in 7.3.1 applying the vertical force of 1100 N for swivelling seats and 600 N for all other seating respectively at the most onerous point along the centre line of the tube, or the middle of the foot rest surface, by any suitable means. For all other seating with foot rests apply the vertical force of 600 N at the most onerous point 60 mm from the edge of the foot rest by means of the local loading pad. For foot rests apply a force of 20 N horizontally outwards along a horizontal line extended forward from the point where the base of the loading pad meets the upper surface of the foot rest.	N/A



Test and Requirements	Test Results
7.3.3 Corner stability test This test is only applicable on seating where it is possible to apply the stability loading pad at the specified position. Where features such as arms prevent the loading pad from being applied at the specified position, the test is not applicable. Position the seating on the floor surface with two adjacent supporting points on the front, or base restrained by stops. The loading point shall be defined as the point 60 mm from the edge of the load bearing structure on a line that passes through the seat loading point and the intersection of lines parallel to the transverse and median planes, projected from the most forward point of the load bearing structure and the side edges of the load bearing structure of the seat at the widest point on the seat at, or in front of, the transverse plane. For seating with a single seat apply a force of 300 N vertically by means of the loading pad acting at the loading point X. For seating with multiple seats apply a force of 300 N at the loading point X on one outside seating position.	N/A
7.3.4 Sideways overbalancing, all seating without arms This test is applicable to all seating where the top edge of the seat on the transverse plane is 50 mm or less above the height of the loaded seat loading point. The transverse plane shall pass through the seat loading point. Position the seating on the floor surface with two adjacent supporting points on one side, or base restrained by stops. Apply a force of 600 N vertically by means of the loading pad at a point 60 mm behind the edge of the load bearing structure on the side nearest the stopped feet and on the transverse plane of the seat. In the transverse plane, apply a sideways force of 20 N horizontally outwards along a line from the point where the base of the loading pad meets the upper surface of the seat.	N/A
7.3.5 Sideways overturning, all other seating 7.3.5.1 General This test is applicable to all seating with arms, or where the top edge of the seat on the transverse plane is more than 50 mm above the height of the seat loading point (A).	
7.3.5.2 Seating with arm rests Position the seating on the floor surface with two adjacent supporting points on one side, or base restrained by stops. Apply a force of 250 N vertically by means of any suitable device, at a point 100 mm to the side of the fore and aft centre line of the seat which is nearest the stopped feet and on the transverse plane. Apply a force of 350 N vertically by any suitable device, at a position on the centre line of the arm up to a maximum 40 mm inwards from the outside edge of the arm structure at the intersection of the arm rest and the transverse plane, but not less than 40 mm from the front or rear edge of the arm structure. If the transverse plane does not intersect with the arm rest, apply the force of 350 N 40 mm from the point at the front or rear of the arm rest structure that is nearest the transverse plane. Apply a horizontal force of 20 N outwards, and perpendicular to the line joining the stopped feet, for at least 5s, at the upper surface of the seat or arm rest in line with the vertical force of 350 N and on the side with stopped feet.	PASS

Test and Requirements	Test Results
7.3.5.3 Seating with raised side edges Position the seating on the floor surface with two adjacent supporting points on one side, or base restrained by stops. Apply a force of 250 N vertically by any suitable device, at a point 100 mm to the side of the fore and aft centre line of the seat which is nearest the stopped feet and on the transverse plane. Apply a force of 350 N by any suitable device, at a position no greater than 40 mm inwards from the outside edge of load bearing structure on the side nearest the stopped feet and on the transverse plane of the seat. If the distance between the loading points is less than 200 mm, a force that provides the same overturning moment of the combined forces, F_1 of 250 N and F_2 of 350 N, shall be applied at the most suitable point on the transverse plane. Apply a horizontal force of 20 N outwards, and perpendicular to the line joining the stopped feet, at the upper surface of the raised edge in line with the vertical force 350 N and on the side with stopped feet.	N/A
7.3.6 Rearwards overturning all seating with back rests The test is not applicable to seating that has adjustable back rest inclination that cannot be locked in position. For seating that has an adjustable back rest inclination that can be locked in position, it shall be locked in the most upright position. When an independent lumbar adjustment is fitted it shall be set in the most adverse configuration. Position the seating on the floor surface with the rear legs, two adjacent supporting points on the back, or base restrained by stops. Apply a vertical force of 600N to the seat by means of the loading pad at the seat loading point (A). Apply the force F_2 horizontally in a rearward direction to the back of the seating at the back loading point, B, or at the top edge of the back rest, whichever is the lower. When the seating has more than one sitting place, carry out the procedure on two most adverse sitting places simultaneously. If the back rest pad is pivoting around a horizontal axis above the height of the seat and is free to move, the horizontal force shall be applied on the axis. If the back rest is height adjustable, the axis shall be set as close as possible to 300 mm above the seat loading point (A).	PASS
7.4 Additional test procedures for seating with reclining back rests 7.4.1 General In addition to the tests in 7.3, seating with reclining back rests shall be subjected to the tests for tilting or reclining, as specified below provided their geometry falls within the reclining angle ranges defined for the appropriate tests. Seating with back rests permanently reclined which fall within the reclining angle ranges for reclining chairs, shall be tested as reclining chairs. The test shall be carried out with the seating in the fully tilted or reclined condition. γ is the angle between the seat and back. θ is the angle of inclination of the back from the horizontal. For seating with shaped or padded seats or backs the load position template shall be used to establish the relevant angles of inclination If the height of the stack of loading discs used in tests 7.4.2, 7.4.3, 7.4.4 and 7.4.5 exceeds the height of the back rest, prevent the upper discs from sliding off by the use of the support.	

Test and Requirements	Test Results
7.4.2 Tilting chairs The test method applies to all values of $\theta \geq 10^\circ$ and values of γ between 90° and 170° . If the seating has a locking system it shall be disabled. Load the seat with the 13 loading discs for swivelling seats and 11 discs for all other seating respectively so that the discs are firmly settled against the back rest. If the height of the stack of discs exceeds the height of the back rest, or if support is needed, prevent the discs from sliding off by the use of the support.	N/A
7.4.3 Reclining seating with leg rest The test method applies to all values of $\theta \geq 10^\circ$ and less than 55° and values of γ between 90° and 170° . All other reclining seating with leg rests shall be treated as tilting seating (7.4.2) With the seating in the fully reclined configuration, load the back of the seat with 8 loading discs by means of the support device and place 3 loading discs onto the leg rest at a distance Z from the intersection of the seat and back.	N/A
7.4.4 Reclining seating without leg rest The test method applies to all values of $\theta \geq 10^\circ$ and less than 45° and values of γ between 90° and 170° . All other reclining seating without foot rests shall be treated as tilting seating (7.4.2). Load the back of the seating with 8 loading discs by means of the support device and place 3 loading discs onto the front of the seat of the chair at a distance X from the intersection of the seat and back.	N/A
7.4.5 Rearwards stability test for rocking chairs This test replaces the rearwards overturning test. Load the chair with the 8 discs so that the discs rest against the chair back. When testing rocking chairs, it may be necessary to restrain the loading discs with lightweight strapping, e.g. tape, string or webbing. Move the chair forwards as far as is practicable or until the back is vertical. Allow the chair to rock rearwards freely under gravity.	N/A
8 Loungers 8.1 General The stability tests defined in Clause 8 are not applicable to loungers which have both a seat height < 200 mm and a mass < 5 kg. The height shall be determined by measuring from the floor to the upper surface of the seating area at the geometrical centre of the lounge loaded with 600 N applied vertically downward using the loading pad. Position the lounge on the floor with its components as specified in Table 3.	
8.2 Requirements When tested according to 8.3, the seating shall not overturn. Where loads are not specified in other standards the requirements contained in Table B.2 shall be used.	
8.3.1 Forward stability Apply a downwards force of 600 N vertically, by means of the loading pad, acting at the point on the median plane of the lounge, 60 mm behind the front edge of the load bearing structure. Apply a force of 20 N horizontally outwards along a horizontal line extended forward from the point where the base of the loading pad meets the upper surface of the seat.	N/A

Test and Requirements	Test Results
8.3.2 Sideways overturning Simultaneously apply vertical forces of 600 N by means of the loading pad, at the points that are on a line 60 mm from one side of the lounge. The first point shall be 300 mm from the front edge of the structure of the lounge, with additional forces applied in 600 mm increments, but at least 300 mm from the rear edge of the lounge. For loungers with arm rests the distance of the vertical force of 600 N shall be at least 300 mm from the front edge of the arm rest construction. If the arm rest is more than 400 mm in length apply additional vertical force of 250 N in the centre of the arm rest.	N/A
7.3.6 Rearwards overturning all seating with back rests The test is not applicable to seating that has adjustable back rest inclination that cannot be locked in position. For seating that has an adjustable back rest inclination that can be locked in position, it shall be locked in the most upright position. When an independent lumbar adjustment is fitted it shall be set in the most adverse configuration. Position the seating on the floor surface with the rear legs, two adjacent supporting points on the back, or base restrained by stops. Apply a vertical force of 600N to the seat by means of the loading pad at the seat loading point (A). Apply the force F_2 horizontally in a rearward direction to the back of the seating at the back loading point, B, or at the top edge of the back rest, whichever is the lower. When the seating has more than one sitting place, carry out the procedure on two most adverse sitting places simultaneously. If the back rest pad is pivoting around a horizontal axis above the height of the seat and is free to move, the horizontal force shall be applied on the axis. If the back rest is height adjustable, the axis shall be set as close as possible to 300 mm above the seat loading point (A).	N/A
7.4.3 Reclining seating with leg rest The test method applies to all values of $\theta \geq 10^\circ$ and less than 55° and values of γ between 90° and 170° . All other reclining seating with leg rests shall be treated as tilting seating (7.4.2) With the seating in the fully reclined configuration, load the back of the seat with 8 loading discs by means of the support device and place 3 loading discs onto the leg rest at a distance Z from the intersection of the seat and back.	N/A

Remark:

1. N/A – Not applicable; N/R – Not requested; N/P – Not provided.
2. For the sample information and pictures, please refer to the following page.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

1-2/F., Building 1, European Industrial Park, No.1, Shunhe South Road, Wusha, Daliang, Shunde District, Foshan, Guangdong, China 528300 t (86-757)22805888 www.sgs.com.cn
中国·广东·佛山市顺德区大良街道办事处五沙社区居民委员会顺和南路1号欧洲工业园一号厂房首层、二层 邮编: 528300 t (86-757)22805888 sgs.china@sgs.com

SAMPLE INFORMATION AND PICTURES

Weight: 24.70 kg

Overall Dimensions: 920 mm D x 1785 mm W x 925 mm H (with cushion) / 845 mm H (without cushion)

Other Dimensions: /

Sample as Received



View 1



View 2



View 3

Unless otherwise stated, the decision rule for conformity reporting is based on Binary Statement for Simple Acceptance Rule ($w=0$) stated in ILAC-G8:09/2019.

End of Report



SGS-TESTING SERVICES
Shunde Branch

Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

1-2/F., Building 1, European Industrial Park, No.1, Shunhe South Road, Wusha, Daliang, Shunde District, Foshan, Guangdong, China 528300 t (86-757)22805888 www.sgs.com.cn
中国·广东·佛山市顺德区大良街道办事处五沙社区居民委员会顺和南路1号欧洲工业园一号厂房首层、二层 邮编: 528300 t (86-757)22805888 sgs.china@sgs.com